



UNIVERSITI PUTRA MALAYSIA

**DETERMINATION OF ENERGY REQUIREMENTS FOR DRY LAND
TILLAGE USING SPATIAL VARIABILITY TECHNIQUE**

NG ENG BOON.

FK 2006 43

**DETERMINATION OF ENERGY REQUIREMENTS
FOR DRY LAND TILLAGE USING
SPATIAL VARIABILITY TECHNIQUE**

By

NG ENG BOON

**Thesis submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirement for the Degree of Master of Science**

March 2006



DEDICATED TO

My wife, daughter and family members



Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the Degree of Master of Science

**DETERMINATION OF ENERGY REQUIREMENTS
FOR DRY LAND TILLAGE USING
SPATIAL VARIABILITY TECHNIQUE**

By

NG ENG BOON

March 2006

Chairman : Associate Professor Azmi Hj. Yahya, PhD

Faculty : Engineering

This study describes the utilization of spatial variability technique in obtaining the tillage energy requirements of disk plowing operation, first rotary tilling after disk plowing operations and second rotary tilling after first rotary tilling and disk plowing operations. Spatial variability of soil terrain characteristics, tractor-implement performances and tillage qualities were measured across two field plots using the mapping system that consists of a Massey Ferguson 3060 instrumented tractor with built-in data acquisition system, differential global positioning system (DGPS) and transducers, mounted-type soil penetrometer-shearometer unit and traileed-type soil surface profile digitizer, respectively. The collected soil terrain characteristic and tractor-implement performance data sets were transferred to ArcView GIS software to produce spatial interpolated surface maps for further statistical analyses. SAS statistical software was used to perform univariate, correlation and stepwise multiple regression analyses to generate mathematical models for tillage energy requirements. Models for tractor travel speed, draft and fuel consumption with respect to the soil terrain characteristic and tractor-implement performance variables were successfully developed for disk plowing operations and

models for tractor travel speed, PTO power and fuel consumption with respect to the soil terrain characteristic and tractor-implement performance variables were successfully developed for first rotary tilling after disk plowing operations and second rotary tilling after first rotary tilling and disk plowing operations. Mean values of soil moisture content, average elevation height, degree of tilth, random roughness index of the soil surface profile, sensing error, PTO power and fuel consumption data sets resulting from first rotary tilling after disk plowing operations and second rotary tilling after first rotary tilling and disk plowing operations at rated and reduced engine speed were also documented for comparison purposes. Evidence trends were shown on soil random roughness index, PTO power, and fuel consumption when subjected to different tillage operations and engine speeds.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PENENTUAN KEPERLUAN TENAGA UNTUK PEMBAJAKAN TANAH
KERING DENGAN KAEDAH PERUBAHAN RUANGAN**

Oleh

NG ENG BOON

Mac 2006

Pengerusi : Profesor Madya Azmi Hj. Yahya, PhD

Faculty : Kejuruteraan

Kajian ini menerangkan penggunaan kaedah perubahan ruangan dalam mendapatkan keperluan tenaga pembajakan bagi operasi-operasi pembajakan bajak piring, operasi-operasi pembajakan bajak putar pertama selepas bajak piring serta operasi-operasi pembajakan bajak putar kedua selepas bajak putar pertama dan bajak piring. Perubahan ruangan bagi sifat-sifat permukaan tanah, kecekapan traktor dan jentera bajak, dan kualiti pembajakan diukur dengan menggunakan sistem pemetaan yang mengandungi sebuah traktor Massey Ferguson 3060 yang dilengkapi dengan sistem instrumentasi, sistem perolehan data, 'differential global positioning system (DGPS)' dan alat-alat penderia, serta satu unit alat penusuk dan pericah tanah jenis sangkut penuh, dan sebuah alat pendigitalan profil permukaan tanah jenis treler bagi dua plot ladang. Set-set data bagi sifat-sifat permukaan tanah dan kecekapan traktor dan jentera bajak yang telah dikumpulkan dan dipindahkan ke perisian "ArcView GIS" untuk menghasilkan peta-peta permukaan daripada interpolasi ruangan bagi analisis-analisis statistik yang seterusnya, Perisian statistik "SAS" digunakan untuk menghasilkan analisis-analisis "univariate", "correlation" dan "stepwise multiple regression" bagi membentuk model-model matematik keperluan tenaga

pembajakan. Model-model kelajuan traktor, rintangan daya tarikan bajak dan kadar gunaan minyak dari segi pertimbangan kepada parameter-parameter sifat permukaan tanah dan kecekapan traktor dan jentera bajak telah berjaya dibentukkan bagi operasi-operasi pembajakan bajak piring dan model-model kelajuan traktor, kuasa PTO dan kadar gunaan minyak dari segi pertimbangan kepada parameter-parameter sifat permukaan tanah dan kecekapan traktor dan jentera bajak telah berjaya dibentukkan bagi operasi-operasi pembajakan bajak putar pertama selepas bajak piring serta operasi-operasi pembajakan bajak putar kedua selepas bajak putar pertama dan bajak piring. Purata bacaan set-set data bagi kandungan air tanah, purata ketinggian aras tanah, darjah kegemburan, index kekasaran rawak bagi profil permukaan tanah, ralat penderiaan, kuasa PTO dan kadar gunaan minyak yang didapatkan daripada operasi-operasi pembajakan bajak putar pertama selepas bajak piring serta operasi-operasi pembajakan bajak putar kedua selepas bajak putar pertama dan bajak piring juga didokumentasikan untuk tujuan perbandingan. Kesan-kesan yang jelas telah ditunjukkan pada index kekasaran rawak, kuasa PTO dan kadar gunaan minyak jika diperhatikan dalam operasi-operasi pembajakan dan kelajuan enjin yang berlainan.

ACKNOWLEDGEMENTS

This research study was carried out to contribute towards the expansion of the knowledge on precision farming. The completion of this thesis would have been impossible if not for the assistance and direct involvement of many kind-hearted individuals. Much appreciation to all my mentors and I have no way of repaying such a debt except to express my sincerest gratitude.

First and foremost, I am very grateful to my supervisor, Assoc. Prof. Dr. Azmi Dato' Yahya, for his valuable comments, patience, guidance, and strong support for the very enriching and thought-provoking discussions which helped to shape the thesis. He was always there to help whenever needed throughout the project. Next, I would also like to thank the other two members in my supervisory committee, Prof. Ir. Dr. Desa Ahmad and Dr. Chan Chee Wan, and three members in my examination committee, Prof. Dr. Shrini K. Upadhyaya, Dr. Rimfiel Janius and Dr. Jamarei Othman for the kind contributions, feedback, and comment in the formulation of this thesis.

Acknowledgement is also extended to IRPA for granting the financial support for my Masters Degree study. For all the lecturers and staffs of the Department of Biological and Agricultural Engineering, Universiti Putra Malaysia, thanks for giving me full commitment and co-operation during the process of doing my Masters Degree project.



I am also indebted to Dr. A. F. Kheiralla who has given various discussions and suggestions which contributed a lot towards the formulation of the experiments and manuscript. My heartfelt thanks also go to Roshdi Zamri, Wee Beng Sui, Gew Soon Kiat, Nar Hai Sin, Darius, Athaur, and Tan Chye Hee and all my fellow friends for their sacrifices, encouragement, and generous co-operation throughout my project.

Thanks are extended to University Agriculture Park (TPU) for granting us the permission to conduct the field test in the corn field of Universiti Putra Malaysia.

I am forever indebted to my beloved family members for their understanding and everlasting love and care during the course of my study.



I certify that an Examination Committee has met on 30th March 2006 to conduct the final examination of Ng Eng Boon on his Master of Science thesis entitled “Determination of Energy Requirements for Dry Land Tillage Using Spatial Variability Technique” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

MUHAMAD SALIH HJ. JA’AFAR, MS

Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

JAMAREI OTHMAN, PhD


Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

RIMFIEL JANIUS, PhD

Lecturer
Faculty of Engineering
Universiti Putra Malaysia
(Internal Examiner)

SHRINI K. UPADHYAYA, PhD

Professor
Biological and Agricultural Engineering Department
University of California, USA
(External Examiner)



HASANAH MOHD. GHAZALI, PhD
Professor/Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: **15 JUN 2006**



This thesis submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirements for the degree of Master of Science. The members of the Supervisory Committee are as follows:

AZMI HJ YAHYA, PhD


Associate Professor
Faculty of Engineering
Universiti Putra Malaysia
(Chairman)

DESA AHMAD, PhD

Professor
Faculty of Engineering
Universiti Putra Malaysia
(Member)

CHAN CHEE WAN, PhD

Center of Mechanization and Automation
Malaysia Agriculture Research and Development Institute (MARDI)
(Member)




AINI IDERIS, PhD
Professor/Dean
School of Graduate Studies
Universiti Putra Malaysia

Date: **13 JUL 2006**

DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



NG ENG BOON

Date: 29. 5. 2006

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL	ix
DECLARATION	xi
LIST OF TABLES	xiv
LIST OF FIGURES	xvi
 CHAPTER	
I INTRODUCTION	1
1.1 Justification	1
1.2 Objectives	4
 II LITERATURE REVIEW	5
2.1 Energy Requirements of Tillage Operation	5
2.1.1 Draft and Energy Requirements	5
2.1.2 PTO Power and Energy Requirements	17
2.2 Formulation of Models	21
2.2.1 Draft Models	21
2.2.2 Fuel and PTO Power Models	29
 III MATERIALS AND METHODS	32
3.1 Mapping System	32
3.1.1 Mapping System for Tractor-implement Performance	34
3.1.2 Mapping System for Soil Terrain Characteristics	35
3.1.3 Mapping System for Tillage Quality	36
3.2 Tractor Pitch and Roll Angles Transducer	37
3.2.1 Calibration Results	42
3.3 Tillage Depth Transducer	48
3.3.1 Calibration Results	53
3.4 Establishment of Global Positioning System Control Point.	57
3.5 Field Experiments	59
3.6 Geographical Information System Analysis	67
3.7 Statistical Analyses and Models Development	69
 IV RESULTS AND DISCUSSIONS	71
4.1 Energy Requirements of Disk Plowing Operations	71
4.2 Energy Requirements of First Rotary Tilling after Disk Plowing Operations	79
4.3 Energy Requirements of Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operations	86
4.4 Spatial Variation of Soil Terrain Characteristic Parameters	95



4.5	Spatial Variation of Tractor-implement Performance Parameters	99
4.6	Tillage Quality of Tillage Operations	124
V	CONCLUSIONS	131
	BIBLIOGRAPHY	136
	APPENDICES	
	BIODATA OF THE AUTHOR	



LIST OF TABLES

Table		Page
2.1	Regression equations for draft of primary tillage in Oklahoma soils	23
2.2	Regression equations for draft of the tandem disk, chisel plow, and field cultivator on a silty clay loam soil	28
3.1	ANOVA for pitch angle transducer output voltage	44
3.2	ANOVA for roll angle transducer output voltage	45
3.3	Regression analysis for pitch angle transducer output voltage	45
3.4	Regression analysis for roll angle transducer output voltage	46
3.5	ANOVA for tillage depth transducer output voltage	55
3.6	Regression analysis for tillage depth transducer output voltage	56
3.7	Surveyed GPS control points	59
4.1	Descriptive statistics of the generated data set for disk plowing operations	75
4.2	Correlation analysis of soil terrain characteristics and tractor-implement performance parameters of disk plowing operations	76
4.3	Multiple regression analysis for tractor travel speed of disk plowing operations	77
4.4	Multiple regression analysis for implement draft of disk plowing operations	77
4.5	Multiple regression analysis for tractor fuel consumption of disk plowing operations	78
4.6	Descriptive statistics of the generated data set for first rotary tilling after disk plowing operations	82
4.7	Correlation analysis of soil terrain characteristics and tractor-implement performance parameters of first rotary tilling after disk plowing operations	83
4.8	Multiple regression analysis for tractor travel speed of first rotary tilling after disk plowing operations	84



4.9	Multiple regression analysis for PTO power of first rotary tilling after disk plowing operations	84
4.10	Multiple regression analysis for tractor fuel consumption of first rotary tilling after disk plowing operations	88
4.11	Descriptive statistics of the generated data set for second rotary tilling after first rotary tilling and disk plowing operations	89
4.12	Correlation analysis of soil terrain characteristics and tractor-implement performance parameters of second rotary tilling after first rotary tilling and disk plowing operations	90
4.13	Multiple regression analysis for tractor travel speed of second rotary tilling after first rotary tilling and disk plowing operations	91
4.14	Multiple regression analysis for PTO power of second rotary tilling after first rotary tilling and disk plowing operations	91
4.15	Multiple regression analysis for tractor fuel consumption of second rotary tilling after first rotary tilling and disk plowing operations	92
4.16	Mean values of soil properties, soil surface profiles, sensing error, PTO power, and fuel consumption resulted from first and second rotary tilling after disk plow operations at rated and reduced engine speed	125

LIST OF FIGURES

Figure		Page
3.1	Configuration of the Mapping System	33
3.2	Configuration of Tractor Pitch and Roll Angles Transducer	38
3.3	Calibration Test of Tractor Pitch and Roll Angles Transducer	39
3.4	Mounting of the Tractor Pitch and Roll Angles Transducer inside Tractor Cab	41
3.5	Calibration Curve for Output Voltage of Pitch Angle Transducer	46
3.6	Calibration Curve for Output Voltage of Roll Angle Transducer	47
3.7	Verification Curve for Measurement Accuracy of Pitch Angle Transducer	47
3.8	Verification Curve for Measurement Accuracy of Roll Angle Transducer	48
3.9	Tillage Depth Transducer with Its L-shape Bracket	50
3.10	Calibration Test of Tillage Depth Transducer	50
3.11	Mounting of the Tillage Depth Transducer and Its L-Shape Bracket on Rockshaft of Tractor	52
3.12	Tractor and Tillage Implement Geometry Before and After Disk Plowing Operation	53
3.13	Calibration Curve for Output Voltage of Tillage Depth Transducer	56
3.14	Verification Curve for Output Voltage of Tillage Depth Transducer	57
3.15	Layout of Surveyed GPS Control Point Locations	58
3.16	Layout of Test Plots	60
3.17	Field Test of the Mounted-type Automated Soil Penetrometer-shearometer Unit	65
3.18	Field Test of the Tractor-implement Performance Mapping System for Disk Plowing Operation	65

3.19	Field Test of the Tractor-implement Performance Mapping System for Rotary Tilling Operation	66
3.20	Field Test of the Trailed-type Automated Soil Surface Profile Digitizer	66
4.1	Spatial Map of Soil Penetration Resistance for Disk Plowing Operation at Rated Engine Speed	96
4.2	Spatial Map of Soil Shear Stress for Disk Plowing Operation at Rated Engine Speed	96
4.3	Spatial Map of Soil Moisture Content for Disk Plowing Operation at Rated Engine Speed	97
4.4	Spatial Map of Soil Penetration Resistance Measurements for Disk Plowing Operation at Reduced Engine Speed	97
4.5	Spatial Map of Soil Shear Stress for Disk Plowing Operation at Reduced Engine Speed	98
4.6	Spatial Map of Soil Moisture Content for Disk Plowing Operation at Reduced Engine Speed	98
4.7	Spatial Map of Tractor Pitch Angle for Disk Plowing Operation at Rated Engine Speed	101
4.8	Spatial Map of Implement Draft for Disk Plowing Operation at Rated Engine Speed	102
4.9	Spatial Map of Tractor Fuel Consumption for Disk Plowing Operation at Rated Engine Speed	102
4.10	Spatial Map of Tractor Travel Speed for Disk Plowing Operation at Rated Engine Speed	103
4.11	Spatial Map of Tractor Wheel Slip for Disk Plowing Operation at Rated Engine Speed	103
4.12	Spatial Map of Tractor Wheel Torque for Disk Plowing Operation at Rated Engine Speed	104
4.13	Spatial Map of Tillage Depth for Disk Plow Operation at Rated Engine Speed	104
4.14	Spatial Map of Tractive Efficiency for Disk Plowing Operation at Rated Engine Speed	105
4.15	Spatial Map of Tractor Pitch Angle for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	105

4.16	Spatial Map of Tractor PTO Torque for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	106
4.17	Spatial Map of Tractor Fuel Consumption for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	106
4.18	Spatial Map of Tractor Travel Speed for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	107
4.19	Spatial Map of Tractor Wheel Slip for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	107
4.20	Spatial Map of Tractor Wheel Torque for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	108
4.21	Spatial Map of Tillage Depth for First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	108
4.22	Spatial Map of Tractor Pitch Angle for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	109
4.23	Spatial Map of Tractor PTO Torque for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	109
4.24	Spatial Map of Tractor Fuel Consumption for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	110
4.25	Spatial Map of Tractor Travel Speed for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	110
4.26	Spatial Map of Tractor Wheel Slip for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	111
4.27	Spatial Map of Tractor Wheel Torque for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	111
4.28	Spatial Map of Tillage Depth for Second Rotary Tilling After First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	112
4.29	Spatial Map of Tractor Pitch Angle for Disk Plowing Operation at Reduced Engine Speed	112

4.30	Spatial Map of Implement Draft for Disk Plowing Operation at Reduced Engine Speed	113
4.31	Spatial Map of Tractor Fuel Consumption for Disk Plowing Operation at Reduced Engine Speed	113
4.32	Spatial Map of Tractor Travel Speed for Disk Plowing Operation at Reduced Engine Speed	114
4.33	Spatial Map of Tractor Wheel Slip for Disk Plowing Operation at Reduced Engine Speed	114
4.34	Spatial Map of Tractor Wheel Torque for Disk Plowing Operation at Reduced Engine Speed	115
4.35	Spatial Map of Tillage Depth for Disk Plowing Operation at Reduced Engine Speed	115
4.36	Spatial Map of Tractive Efficiency for Disk Plowing Operation at Reduced Engine Speed	116
4.37	Spatial Map of Tractor's Pitch Angle for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	116
4.38	Spatial Map of Tractor PTO Torque for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	117
4.39	Spatial Map of Tractor Fuel Consumption for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	117
4.40	Spatial Map of Tractor Travel Speed for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	118
4.41	Spatial Map of Tractor Wheel Slip for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	118
4.42	Spatial Map of Tractor Wheel Torque for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	119
4.43	Spatial Map of Tillage Depth for First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	119
4.44	Spatial Map of Tractor Pitch Angle for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	120
4.45	Spatial Map of Tractor PTO Torque for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	120

4.46	Spatial Map of Tractor Fuel Consumption for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	121
4.47	Spatial Map of Tractor Travel Speed for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	121
4.48	Spatial Map of Tractor Wheel Slip for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	122
4.49	Spatial Map of Tractor Wheel Torque for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	122
4.50	Spatial Map of Tillage Depth for Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	123
4.51	DEM Model of Soil Surface Profile Produced by First Rotary Tilling after Disk Plowing Operation at Rated Engine Speed	129
4.52	DEM Model of Soil Surface Profile Produced by Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Rated Engine Speed	129
4.53	DEM Model of Soil Surface Profile Produced by First Rotary Tilling after Disk Plowing Operation at Reduced Engine Speed	130
4.54	DEM Model of Soil Surface Profile Produced by Second Rotary Tilling after First Rotary Tilling and Disk Plowing Operation at Reduced Engine Speed	130

CHAPTER I

INTRODUCTION

1.1 Justification

Soil information such as soil quality, soil strength, soil property and so on is an important element in daily agricultural activities. For instance, farmers always check the soil quality of an agricultural field by means of visual inspection of the field or feeling the soil in the hand before any tillage operation is carried out. This technique may result in considerable error in determining the extent of tillage operation need to be conducted based on the known soil quality. Excessive tillage could cause damage in the soil structure and high energy expenses in the operation. On the other hand, inadequate tillage may results with regions of poor soil quality within the field plot. The existence of uneven soil quality distribution within an area could affect the growth of the germinated seeds and ultimately affects its total crop yield.

Much progress has been made in soil and tillage studies, particularly in tillage energy requirements, to understand the relationships between soil physical parameters and tractor-implement performances for different tillage implements and operations, soil conditions and seedbed preparations. For example, researchers had successfully developed an agricultural machinery management data in ASAE standard D497 which could provide mathematical expressions for draft and power requirements for tillage implements in several soil types (ASAE, 2003b). However,

the draft equation provided by ASAE standard D497 only involve two parameters namely tractor travel speed and tillage depth and neglect other possible important soil parameters such as soil penetration resistance and soil moisture content and also other possible machine parameters such as drive wheel torques, drive wheel slippages, and pitch and roll angles. Currently, attempt had been made by researchers to quantify spatial variability of both soil and machine parameters using global positioning system (GPS), data logging system and sensors on board an agricultural tractor. This new technology and technique allows high density of spatial variability of field parameters to be collected within a considerable time period and the collected field parameters are able to be illustrated and analyzed in spatial maps basis. McLaughlin and Burt (2000) carried out a study in spatial mapping of tillage energy and reported that draft, fuel consumption, engine speed and forward speed were closely related and maps of these four tractor-implement performance parameters showed similar patterns. Similar study was also done by Sirjacobs *et al.* (2001) to map the spatial variability of draft force, vertical force and moment and correlate them with penetrometry index, gravimetric water content, bulk density, cohesion and internal friction angle, simple compression resistance, Atterberg limits, granulometry and pF curves. They stated that significant relationships were established between a global penetrometry index and the draft force and moment solicitations measured by the sensor, and between gravimetric water content and the vertical force. Therefore, it is hope that with the recent available technology, a study in spatial variability of the field attributes for a particular tillage operation using both geographical information system (GIS) and statistical analysis methods could be carried out to produce a better soil-tillage relationship in a quantitative manner.

Generally, dry land in Malaysia is defined as a typical agricultural field used for vegetable cultivation. Average moisture content in dry basis and annual precipitation in this agricultural land are about 20% and 3000mm, respectively. Conventional tillage operation practices in preparing a crop seedbed in a Malaysian dry land involve disk plowing and rotary tilling operations. Nevertheless, farmers run the tillage operation using traditional practices (i.e. rotary tillage after disk plowing or double rotary tillage after disk plowing) without realizing that excessive tillage energy had been applied resulting in the increased cost and duration of operation. Determination of energy requirements of rotary tillage after disk plowing and double rotary tillage after disk plowing taking into account the correlation between soil physical parameters, tractor-implement performance and tillage quality in a scientifically proven study is therefore an interest to researchers. Traditional methods under controlled field experiment with the involved tractor-implements were time consuming, labourious and could be almost impossible because it involves a lot of parameters. Thus to overcome this problem, a precise system that is equipped on a tractor, capable of measuring the spatial variability of soil physical parameters, tractor-implement performance and tillage quality, and could be used practically in field condition is required to quantify the energy requirements for tillage operations.

The Department of Biological and Agricultural Engineering, Universiti Putra Malaysia has developed a mapping system that consists of a data acquisition system and differential global positioning system (DGPS) on board a Massey Ferguson 3060 tractor for mapping soil terrain characteristics, tractor-implement performances

and tillage qualities, allowing analyses to be done on a spatial basis. However, the mapping system is not equipped with the terrain slope and tillage depth transducers. The measurements of terrain slope and tillage depth were highlighted in the past researcher works as the important variables that contribute to the correlation relationship among the tractor-implement performance and soil terrain parameters. Thus, it is essential to develop these two transducers to the mapping system. This research work is conducted to quantify the energy requirements for dry land tillage using spatial variability technique.

1.2 Objectives

The objectives of the study are as follows:

1. To determine the energy requirements of disk plowing operation, single rotary tillage after disk plowing operations and double rotary tillage after disk plowing operations using spatial variability technique
2. To evaluate spatial relationships between tillage energy requirements and soil terrain characteristics
3. To determine the tillage quality of a single rotary tillage after disk plowing operation and a double rotary tillage after disk plowing operation